

# FARBEX chlorinated rubber finish

FBX102

## intended uses

As a quick drying chemical resistant finish for use in breweries, factories, abattoirs etc where high humidity rules out conventional paints.

## product description

Chlorinated rubber binder pigmented with inorganic pigments and thinned with aromatic hydrocarbon solvent.

## product information

<b>Product reference</b>	FBX102
<b>Volume solids</b>	40%
<b>Typical thickness</b>	35 microns dft from 90 microns wet
<b>Theoretical coverage</b>	11 square metres per litre
<b>Practical coverage</b>	9 square metres per litre
<b>Appearance/Colour range</b>	Gloss finish/White and selected BS4800 colours
<b>VOC content</b>	

## application details

<b>Mix ratio</b>	N/A			
<b>Method of application</b>	Brush or airless spray (0.015" tip and 2500 psi atomising pressure)			
<b>Thinner</b>	Tor TH25 (when required)			
<b>Cleaner</b>	Tor TH19 for cleaning equipment			
<b>Pot Life</b>	N/A			
<b>Drying time</b>				
Substrate Temperature	<b>Touch Dry</b>	<b>Hard Dry</b>	<b>Overcoating Interval</b>	
			<b>Minimum</b>	<b>Maximum</b>
20°C	1 hour	3 hours	2-3 hours	Unlimited

**Note:** Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

## storage and handling

<b>Storage</b>	Store in a safe place out of the reach of children
<b>Pack Size</b>	5 litres and 20 litres
<b>Flash point</b>	Above 32°C
<b>Product weight</b>	1.30 kilos/litre
<b>Shelf life</b>	2 years in unopened containers

## surface preparation

FARBEX Chlorinated Rubber Finish should only be applied to substrates which have been correctly prepared and primed with the appropriate chlorinated rubber primer.

## limitations

Dry film remains sensitive to solvents, oil and fats.

Only comparatively thin films result from this product and therefore multi coats may be required for adequate protection or "high build" types considered.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

## definitions

### **Tolerances**

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### **Practical coverage**

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

### **Pot Life**

Applies only to two component products and refers to the time the mixture remains usable.

## disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall FARBEX Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated: February  
2000**