

FARBEX Chlorinated Rubber Line Marking Paint

intended uses

As a quick drying line marking paint for use on bare concrete, asphalt or painted floors.

product description

A single pack chlorinated rubber resin, pigmented with organic and inorganic and selected extenders.

product information

Product reference

Volume solids	50%
Typical thickness	125 microns dry film thickness
Theoretical coverage	4m ² /litre
Practical coverage	Dependant on substrate
Appearance/Colour range	White/Yellow - Matt
VOC content	410 grams/litre

application details

Mix ratio	N/A
Method of application	Roller or airless spray (thin using 5 to 10% thinners for spraying)
Thinner	Xylene Mixture
Cleaner	Gunwash
Pot Life	N/A

Drying time

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
20°C	15-20 minutes		None	None

Note: Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

storage and handling

Storage

Store the closed containers in a store room which is either in a safe place or is a fire resisting structure. The storage and conditions must meet the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Pack Size	5 litres
Flash point	Below 21°C. Highly Flammable
Product weight	1.6 kgs/litre depending on colour
Shelf life	

surface preparation

Surfaces must be clean, dry and free from oil and grease contamination, loose dust or laitance. Acid etch concrete if in doubt to remove heavy laitance.

limitations

1. Yellow contains lead chrome pigments.
2. Must be stored in accordance with the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

definitions

Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

Pot Life

Applies only to two component products and refers to the time the mixture remains usable.

disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied

